

# Package: enviGCMS (via r-universe)

October 9, 2026

**Type** Package

**Title** GC/LC-MS Data Analysis for Environmental Science

**Version** 0.9.1

**Description** Gas/Liquid Chromatography-Mass Spectrometer(GC/LC-MS) Data Analysis for Environmental Science. This package covered topics such molecular isotope ratio, matrix effects and Short-Chain Chlorinated Paraffins analysis etc. in environmental analysis.

**URL** <https://yufree.github.io/enviGCMS/>

**BugReports** <https://github.com/yufree/enviGCMS/issues>

**License** GPL-2

**Encoding** UTF-8

**LazyData** true

**Suggests** knitr, testthat, plotly, shiny, rmarkdown, DT, crosstalk, animation, mixtools, RaMS

**VignetteBuilder** knitr

**Depends** R (>= 3.5)

**Imports** Rcpp, BiocParallel, grDevices, graphics, stats, utils, RColorBrewer, data.table, igraph

**LinkingTo** Rcpp

**Config/roxygen2/version** 8.1.1

**Config/pak/sysreqs** libglpk-dev libxml2-dev

**Repository** <https://yufree.r-universe.dev>

**Date/Publication** 2026-10-09 14:24:20 UTC

**RemoteUrl** <https://github.com/yufree/envigcms>

**RemoteRef** HEAD

**RemoteSha** 0b46f157b3638ae5c247f888c2e5f6aeb109c643

## Contents

|                            |    |
|----------------------------|----|
| c.mzrt . . . . .           | 3  |
| checkGoldenRules . . . . . | 4  |
| cleanMGF . . . . .         | 5  |
| findline . . . . .         | 6  |
| findlipid . . . . .        | 7  |
| findmet . . . . .          | 7  |
| findohc . . . . .          | 8  |
| findpfc . . . . .          | 9  |
| getalign . . . . .         | 10 |
| getalign2 . . . . .        | 10 |
| getcompare . . . . .       | 11 |
| getcsv . . . . .           | 12 |
| getdoe . . . . .           | 13 |
| getdwus . . . . .          | 14 |
| getfilter . . . . .        | 14 |
| getformula . . . . .       | 15 |
| getHRMF . . . . .          | 16 |
| getimputation . . . . .    | 17 |
| getintegration . . . . .   | 18 |
| getisotopologues . . . . . | 19 |
| getmass . . . . .          | 20 |
| getmassdefect . . . . .    | 20 |
| getmdh . . . . .           | 21 |
| getmdr . . . . .           | 21 |
| getmslanno . . . . .       | 22 |
| getMSP . . . . .           | 23 |
| getmzrtcsv . . . . .       | 23 |
| getoverlappeak . . . . .   | 24 |
| getpn . . . . .            | 24 |
| getpower . . . . .         | 25 |
| getpqi . . . . .           | 26 |
| getrange . . . . .         | 26 |
| getretcor . . . . .        | 27 |
| getrmd . . . . .           | 27 |
| gifmr . . . . .            | 28 |
| HRMF . . . . .             | 29 |
| integration . . . . .      | 31 |
| list . . . . .             | 31 |
| ma . . . . .               | 32 |
| matrix . . . . .           | 32 |
| plotcc . . . . .           | 33 |
| plotden . . . . .          | 33 |
| plotdwus . . . . .         | 34 |
| plotEIC . . . . .          | 34 |
| plotgroup . . . . .        | 35 |
| plothist . . . . .         | 36 |

|                           |           |
|---------------------------|-----------|
| plothm . . . . .          | 36        |
| plotint . . . . .         | 37        |
| plotintslope . . . . .    | 37        |
| plotkms . . . . .         | 38        |
| plotmr . . . . .          | 38        |
| plotmrc . . . . .         | 39        |
| plotms . . . . .          | 40        |
| plotmz . . . . .          | 40        |
| plotpca . . . . .         | 41        |
| plotpeak . . . . .        | 42        |
| plotridge . . . . .       | 43        |
| plotridges . . . . .      | 43        |
| plotrla . . . . .         | 44        |
| plotsd . . . . .          | 45        |
| plotrug . . . . .         | 45        |
| plotsms . . . . .         | 46        |
| plotsub . . . . .         | 46        |
| plott . . . . .           | 47        |
| plottic . . . . .         | 47        |
| plotTopMS1Peaks . . . . . | 48        |
| plotTopMS2Peaks . . . . . | 49        |
| runMDPlot . . . . .       | 50        |
| runscvp . . . . .         | 50        |
| sccp . . . . .            | 51        |
| scoreIsotopes . . . . .   | 51        |
| TBBPA . . . . .           | 52        |
| writeMSP . . . . .        | 53        |
| <b>Index</b>              | <b>54</b> |

---

|        |                                 |
|--------|---------------------------------|
| c.mzrt | <i>c method for mzrt object</i> |
|--------|---------------------------------|

---

## Description

c method for mzrt object

## Usage

```
## S3 method for class 'mzrt'
c(x, ...)
```

## Arguments

|     |                                     |
|-----|-------------------------------------|
| x   | an mzrt object                      |
| ... | further mzrt objects to concatenate |

**Value**

a combined mzrt object

---

|                  |                                                                |
|------------------|----------------------------------------------------------------|
| checkGoldenRules | <i>Check Chemical Formula against Fiehn Seven Golden Rules</i> |
|------------------|----------------------------------------------------------------|

---

**Description**

Evaluates whether a candidate chemical formula satisfies heuristic chemical rules based on Senior's valence rules (Senior 1951), Hydrogen-to-Carbon (H/C) ratios, heteroatom ratios (N/C, O/C, P/C, S/C, Halogen/C), and Double Bond Equivalents (DBE) as described by Kind & Fiehn (2007).

**Usage**

```
checkGoldenRules(formula, z = 0, min_hc = 0.1, max_hc = 6, max_dbe = 40)
```

**Arguments**

|         |                                                                   |
|---------|-------------------------------------------------------------------|
| formula | Character string representing molecular formula (e.g. "C6H12O6"). |
| z       | Integer charge state (default: 0).                                |
| min_hc  | Numeric minimum H/C ratio (default: 0.1).                         |
| max_hc  | Numeric maximum H/C ratio (default: 6.0).                         |
| max_dbe | Numeric maximum DBE (default: 40.0).                              |

**Value**

A list containing booleans indicating whether the formula passed Senior rules, H/C ratio, heteroatom ratios, DBE, nitrogen rule, and overall validity.

**References**

Kind, T., Fiehn, O. Seven Golden Rules for heuristic filtering of molecular formulas obtained by accurate mass spectrometry. BMC Bioinformatics 8, 105 (2007). doi:[10.1186/147121058105](https://doi.org/10.1186/147121058105)

Senior, J. K. Partitions and their connection with the problems of chemical structure. J. Chem. Phys. 19, 865-873 (1951).

**Examples**

```
checkGoldenRules("C6H12O6")  
checkGoldenRules("C3H32N12O3") # chemically impossible formula
```

---

cleanMGF*Clean an MGF file by keeping only formula-explainable peaks*

---

## Description

For each MS2 spectrum, the precursor neutral mass is derived from PEPMASS, CHARGE and the supplied adduct, candidate parent formulae are enumerated with the native HORIZON engine, and fragment peaks that can be explained as sub-formulae of the best candidate (the one explaining the most peaks) are kept. Spectra without PEPMASS or without any candidate formula are written back unchanged.

## Usage

```
cleanMGF(  
  file,  
  out_file = NULL,  
  adduct = "[M+H]+",  
  charge = NULL,  
  mass_accuracy = 5,  
  elements = "CHNOPS",  
  max_candidates = 3,  
  intensity_cutoff = 0,  
  min_peaks = 2  
)
```

## Arguments

|                  |                                                                                                                                  |
|------------------|----------------------------------------------------------------------------------------------------------------------------------|
| file             | character. Path to an MGF file.                                                                                                  |
| out_file         | character. Output MGF path. Default NULL writes <file stem>_clean.mgf next to the input file.                                    |
| adduct           | character. Single adduct name (see <a href="#">HRMF</a> ), e.g. "[M+H]+". Fragments are assumed singly-charged with this adduct. |
| charge           | integer. Precursor charge state used when the CHARGE header is missing. Default NULL uses 1 (from the adduct sign).              |
| mass_accuracy    | numeric. Mass accuracy in ppm for both precursor decomposition and fragment matching. Default 5.                                 |
| elements         | character. Elements allowed in precursor formula enumeration, e.g. "CHNOPS". Default "CHNOPS".                                   |
| max_candidates   | integer. Maximum number of precursor formula candidates to evaluate per spectrum. Default 3.                                     |
| intensity_cutoff | numeric. Discard peaks below this absolute intensity before annotation. Default 0 (keep all).                                    |
| min_peaks        | integer. Drop spectra left with fewer than this many peaks after cleaning. Default 2.                                            |

## Details

The cleaned file preserves the original header lines and peak line formatting; the chosen parent formula is appended as a FORMULA= header when a candidate is found.

## Value

Invisibly, a data.frame with one row per spectrum: title, pepmass, charge, chosen formula, peak counts before/after, kept fraction and status ("cleaned", "kept" = unchanged, or "dropped").

## See Also

[HRMF](#), [getMSP](#)

## Examples

```
## Not run:
summary <- cleanMGF("ms2.mgf", adduct = "[M+H]+")
summary[, c("title", "formula", "n_before", "n_kept", "status")]

## End(Not run)
```

---

findline

*find line of the regression model for GC-MS*

---

## Description

find line of the regression model for GC-MS

## Usage

```
findline(data, threshold = 2, temp = c(100, 320))
```

## Arguments

|           |                                                   |
|-----------|---------------------------------------------------|
| data      | imported data matrix of GC-MS                     |
| threshold | the threshold of the response (log based 10)      |
| temp      | the scale of the oven temperature (constant rate) |

## Value

list linear regression model for the matrix

## Examples

```
## Not run:
data(matrix)
findline(matrix)

## End(Not run)
```

---

|           |                                                                                |
|-----------|--------------------------------------------------------------------------------|
| findlipid | <i>Find lipid class of metabolites base on referenced Kendrick mass defect</i> |
|-----------|--------------------------------------------------------------------------------|

---

**Description**

Find lipid class of metabolites base on referenced Kendrick mass defect

**Usage**

```
findlipid(list, mode = "pos")
```

**Arguments**

|      |                                                                                                                          |
|------|--------------------------------------------------------------------------------------------------------------------------|
| list | list with data as peaks list, mz, rt and group information, retention time should be in seconds                          |
| mode | 'pos' for positive mode, 'neg' for negative mode and 'none' for neutral mass, only support [M+H] and [M-H] for each mode |

**Value**

list list with dataframe with the lipid referenced Kendrick mass defect(RKMD) and logical for class

**References**

Method for the Identification of Lipid Classes Based on Referenced Kendrick Mass Analysis. Lerno LA, German JB, Lebrilla CB. Anal Chem. 2010 May 15;82(10):4236-45.

**Examples**

```
data(list)
RKMD <- findlipid(list)
```

---

|         |                                          |
|---------|------------------------------------------|
| findmet | <i>Screen metabolites by Mass Defect</i> |
|---------|------------------------------------------|

---

**Description**

Screen metabolites by Mass Defect

**Usage**

```
findmet(list, mass, mdr = 50)
```

**Arguments**

|      |                                                                                                 |
|------|-------------------------------------------------------------------------------------------------|
| list | list with data as peaks list, mz, rt and group information, retention time should be in seconds |
| mass | mass to charge ratio of specific compounds                                                      |
| mdr  | mass defect range, default 50mDa                                                                |

**Value**

list with filtered metabolites mass to charge index of certain compound

---

findohc

---

*Screen organohalogen compounds*


---

**Description**

Screen organohalogen compounds by retention time, mass defect analysis and isotope relationship modified by literature report. Also support compounds with [M] and [M+2] ratio cutoff.

**Usage**

```
findohc(
  list,
  sf = 78/77.91051,
  step = 0.001,
  stepsd1 = 0.003,
  stepsd2 = 0.005,
  mzc = 700,
  cutoffint = 1000,
  cutofffr = 0.4,
  clusterfcf = 10
)
```

**Arguments**

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| list       | list with data as peaks list, mz, rt and group information, retention time should be in seconds     |
| sf         | scale factor, default 78/77.91051(Br)                                                               |
| step       | mass defect step, default 0.001                                                                     |
| stepsd1    | mass defect uncertainty for lower mass, default 0.003                                               |
| stepsd2    | mass defect uncertainty for higher mass, default 0.005                                              |
| mzc        | threshold of lower mass and higher mass, default 700                                                |
| cutoffint  | the cutoff of intensity, default 1000                                                               |
| cutofffr   | the cutoff of [M] and [M+2] ratio, default 0.4                                                      |
| clusterfcf | the cutoff of cluster analysis to separate two different ions groups for retention time, default 10 |

**Value**

list with filtered organohalogen compounds

**References**

Identification of Novel Brominated Compounds in Flame Retarded Plastics Containing TBBPA by Combining Isotope Pattern and Mass Defect Cluster Analysis Ana Ballesteros-Gomez, Joaquin Ballesteros, Xavier Ortiz, Willem Jonker, Rick Helmus, Karl J. Jobst, John R. Parsons, and Eric J. Reiner Environmental Science & Technology 2017 51 (3), 1518-1526 DOI: 10.1021/acs.est.6b03294

---

findpfc

*Find PFCs based on mass defect analysis*

---

**Description**

Find PFCs based on mass defect analysis

**Usage**

```
findpfc(list)
```

**Arguments**

|                   |                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------|
| <code>list</code> | list with data as peaks list, mz, rt and group information, retention time should be in seconds |
|-------------------|-------------------------------------------------------------------------------------------------|

**Value**

list list with potential PFCs compounds index

**References**

Liu, Y.; D'Agostino, L. A.; Qu, G.; Jiang, G.; Martin, J. W. High-Resolution Mass Spectrometry (HRMS) Methods for Nontarget Discovery and Characterization of Poly- and per-Fluoroalkyl Substances (PFASs) in Environmental and Human Samples. TrAC Trends in Analytical Chemistry 2019, 121, 115420.

**Examples**

```
data(list)
pfc <- findpfc(list)
```

---

|          |                                                                              |
|----------|------------------------------------------------------------------------------|
| getalign | <i>Align two peaks vectors by mass to charge ratio and/or retention time</i> |
|----------|------------------------------------------------------------------------------|

---

**Description**

Align two peaks vectors by mass to charge ratio and/or retention time

**Usage**

```
getalign(mz1, mz2, rt1 = NULL, rt2 = NULL, ppm = 10, deltart = 10)
```

**Arguments**

|         |                                                |
|---------|------------------------------------------------|
| mz1     | the mass to charge of reference peaks          |
| mz2     | the mass to charge of peaks to be aligned      |
| rt1     | retention time of reference peaks              |
| rt2     | retention time of peaks to be aligned          |
| ppm     | mass accuracy, default 10                      |
| deltart | retention time shift table, default 10 seconds |

**Value**

data frame with aligned peaks table

**Examples**

```
mz1 <- c(221.1171, 227.1390, 229.1546, 233.1497, 271.0790 )
mz2 <- c(282.279, 281.113, 227.139, 227.139, 302.207)
rt1 <- c(590.8710, 251.3820, 102.9230, 85.8850, 313.8240)
rt2 <- c(787.08, 160.02, 251.76, 251.76, 220.26)
getalign(mz1,mz2,rt1,rt2)
```

---

|           |                                                                              |
|-----------|------------------------------------------------------------------------------|
| getalign2 | <i>Align mass to charge ratio and/or retention time to remove redundancy</i> |
|-----------|------------------------------------------------------------------------------|

---

**Description**

Align mass to charge ratio and/or retention time to remove redundancy

**Usage**

```
getalign2(mz, rt, ppm = 5, deltart = 5)
```

**Arguments**

|         |                                                |
|---------|------------------------------------------------|
| mz      | the mass to charge of reference peaks          |
| rt      | retention time of reference peaks              |
| ppm     | mass accuracy, default 10                      |
| deltart | retention time shift table, default 10 seconds |

**Value**

index for

**Examples**

```
mz <- c(221.1171, 221.1170, 229.1546, 233.1497, 271.0790 )
rt <- c(590.8710, 587.3820, 102.9230, 85.8850, 313.8240)
getalign2(mz,rt)
```

---

getcompare

*Align multiple peaks list to one peak list*

---

**Description**

Align multiple peaks list to one peak list

**Usage**

```
getcompare(..., index = 1, ppm = 5, deltart = 5)
```

**Arguments**

|         |                                                |
|---------|------------------------------------------------|
| ...     | peaks list, mzrt objects                       |
| index   | numeric, the index of reference peaks.         |
| ppm     | pmd mass accuracy, default 5                   |
| deltart | retention time shift table, default 10 seconds |

**Value**

list object with aligned mzrt objects

---

`getcsv`*Convert an list object to csv file*

---

**Description**

Convert an list object to csv file

**Usage**

```
getcsv(list, name, mzdigit = 4, rtdigit = 1, type = "o", target = FALSE, ...)
```

**Arguments**

|                      |                                                                                                                                                                                                                                                                                                          |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>list</code>    | list with data as peaks list, mz, rt and group information                                                                                                                                                                                                                                               |
| <code>name</code>    | result name for csv and/or eic file, default NULL                                                                                                                                                                                                                                                        |
| <code>mzdigit</code> | m/z digits of row names of data frame, default 4                                                                                                                                                                                                                                                         |
| <code>rtdigit</code> | retention time digits of row names of data frame, default 1                                                                                                                                                                                                                                              |
| <code>type</code>    | csv format for further analysis, m means Metaboanalyst, a means xMSannotator, p means Mummichog(NA values are imputed by 'getimputation', and F test is used here to generate stats and p value), o means full information csv (for 'pmd' package), default o. mapo could output all those format files. |
| <code>target</code>  | logical, preserve original rowname of data or not for target data, default FALSE.                                                                                                                                                                                                                        |
| <code>...</code>     | other parameters for 'write.table'                                                                                                                                                                                                                                                                       |

**Value**

NULL, csv file

**References**

Li, S.; Park, Y.; Duraisingham, S.; Strobel, F. H.; Khan, N.; Soltow, Q. A.; Jones, D. P.; Pulendran, B. PLOS Computational Biology 2013, 9 (7), e1003123. Xia, J., Sinelnikov, I.V., Han, B., Wishart, D.S., 2015. MetaboAnalyst 3.0 - making metabolomics more meaningful. Nucl. Acids Res. 43, W251-W257.

**Examples**

```
## Not run:  
data(list)  
getcsv(list,name='demo')  
  
## End(Not run)
```

---

|        |                                                                         |
|--------|-------------------------------------------------------------------------|
| getdoe | <i>Generate the group level rsd and average intensity based on DoE,</i> |
|--------|-------------------------------------------------------------------------|

---

## Description

Generate the group level rsd and average intensity based on DoE,

## Usage

```
getdoe(  
  list,  
  inscf = 5,  
  rsdcf = 100,  
  rsdcft = 30,  
  imputation = "1",  
  tr = FALSE,  
  BPPARAM = BiocParallel::bpparam()  
)
```

## Arguments

|            |                                                                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| list       | list with data as peaks list, mz, rt and group information                                                                                                      |
| inscf      | Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5 |
| rsdcf      | the rsd cutoff of all peaks in all group                                                                                                                        |
| rsdcft     | the rsd cutoff of all peaks in technical replicates                                                                                                             |
| imputation | parameters for 'getimputation' function method                                                                                                                  |
| tr         | logical. TRUE means dataset with technical replicates at the base level folder                                                                                  |
| BPPARAM    | An optional BiocParallelParam instance determining the parallel back-end to be used during evaluation.                                                          |

## Value

list with group mean, standard deviation, and relative standard deviation for all peaks, and filtered peaks index

## See Also

[getimputation](#), [getpower](#)

## Examples

```
data(list)  
getdoe(list)
```

---

|          |                                                  |
|----------|--------------------------------------------------|
| getdwtus | <i>Density weighted intensity for one sample</i> |
|----------|--------------------------------------------------|

---

**Description**

Density weighted intensity for one sample

**Usage**

```
getdwtus(peak, n = 512, log = FALSE)
```

**Arguments**

|      |                                                                                          |
|------|------------------------------------------------------------------------------------------|
| peak | peaks intensity one sample                                                               |
| n    | the number of equally spaced points at which the density is to be estimated, default 512 |
| log  | log transformation                                                                       |

**Value**

Density weighted intensity for one sample

**Examples**

```
data(list)
getdwtus(list$data[,1])
```

---

|           |                                                      |
|-----------|------------------------------------------------------|
| getfilter | <i>Filter the data based on row and column index</i> |
|-----------|------------------------------------------------------|

---

**Description**

Filter the data based on row and column index

**Usage**

```
getfilter(list, rowindex = TRUE, colindex = TRUE, name = NULL, type = "o", ...)
```

**Arguments**

|          |                                                                                                                                                                                                                                                                                                          |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| list     | list with data as peaks list, mz, rt and group information                                                                                                                                                                                                                                               |
| rowindex | logical, row index to keep                                                                                                                                                                                                                                                                               |
| colindex | logical, column index to keep                                                                                                                                                                                                                                                                            |
| name     | file name for csv and/or eic file, default NULL                                                                                                                                                                                                                                                          |
| type     | csv format for further analysis, m means Metaboanalyst, a means xMSannotator, p means Mummichog(NA values are imputed by 'getimputation', and F test is used here to generate stats and p value), o means full information csv (for 'pmd' package), default o. mapo could output all those format files. |
| ...      | other parameters for 'getcsv'                                                                                                                                                                                                                                                                            |

**Value**

list with remain peaks, and filtered peaks index

**See Also**

[getimputation](#), [getcsv](#)

**Examples**

```
data(list)
li <- getdoe(list)
lif <- getfilter(li, rowindex = li$rsdindex)
```

---

|            |                                                                                  |
|------------|----------------------------------------------------------------------------------|
| getformula | <i>Get chemical formula for mass to charge ratio using the HORIZON algorithm</i> |
|------------|----------------------------------------------------------------------------------|

---

**Description**

Rapidly decomposes accurate mass-to-charge ratios into candidate chemical formulas using the native HORIZON (Heavy-first Ordered Recursive Inference with Zero-loop Optimal Navigation) engine. Supports chemical plausibility filtering via Double Bond Equivalent (DBE), Nitrogen rule, and Kind & Fiehn Seven Golden Rules.

**Usage**

```
getformula(
  mz,
  charge = 0,
  window = 0.001,
  elements = list(C = c(1, 50), H = c(1, 50), N = c(0, 50), O = c(0, 50), P = c(0, 1), S
    = c(0, 1)),
  golden_rules = TRUE,
  detailed = FALSE,
```

```
    resolution = 0,  
    nthreads = 1  
  )
```

### Arguments

|              |                                                                                                                                                                                                               |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mz           | a vector with mass to charge ratio                                                                                                                                                                            |
| charge       | The charge value of the formula, default 0 for autodetect                                                                                                                                                     |
| window       | The window accuracy in the same units as mass                                                                                                                                                                 |
| elements     | Elements list to take into account.                                                                                                                                                                           |
| golden_rules | logical, whether to filter by Fiehn Seven Golden Rules (default: TRUE)                                                                                                                                        |
| detailed     | logical, if TRUE return a list of data.frames with formula, exact mass, error, DBE, H/C ratio, Senior rules, and validation details; if FALSE (default), return a list of character vectors of valid formulas |
| resolution   | numeric, mass spectrometer resolving power for isotope peak merging (default: 0)                                                                                                                              |
| nthreads     | integer, number of OpenMP parallel threads for batch processing (default: 1)                                                                                                                                  |

### Value

list of chemical formulas (or data.frames if detailed = TRUE)

---

|         |                                                                              |
|---------|------------------------------------------------------------------------------|
| getHRMF | <i>Batch High Resolution Mass Filtering for all compounds in an MSP file</i> |
|---------|------------------------------------------------------------------------------|

---

### Description

Applies [HRMF](#) to every compound in an MSP file that has a chemical formula annotation.

### Usage

```
getHRMF(  
  file,  
  charge = 1,  
  adduct = NULL,  
  mass_accuracy = 5,  
  intensity_cutoff = 1,  
  IR_RelAb_cutoff = 1  
)
```

### Arguments

|                  |                                                                                                                           |
|------------------|---------------------------------------------------------------------------------------------------------------------------|
| file             | character. Path to an MSP file.                                                                                           |
| charge           | integer. Charge state (see <a href="#">HRMF</a> ). Default 1. Ignored when adduct is supplied.                            |
| adduct           | character vector of adduct names or named numeric vector of custom mass deltas (see <a href="#">HRMF</a> ). Default NULL. |
| mass_accuracy    | numeric. Mass accuracy in ppm. Default 5.                                                                                 |
| intensity_cutoff | numeric. Minimum absolute intensity. Default 1.                                                                           |
| IR_RelAb_cutoff  | numeric. Relative abundance cutoff (%) for theoretical isotopologues. Default 1.                                          |

### Value

A named list where each element contains the HRMF results for one compound (with a valid formula) from the MSP file.

### See Also

[HRMF](#), [getMSP](#)

### Examples

```
## Not run:
results <- getHRMF("library.msp")

# LC-MS/MS library with protonated ions
results <- getHRMF("library.msp", adduct = "[M+H]+")

## End(Not run)
```

---

|               |                                   |
|---------------|-----------------------------------|
| getimputation | <i>Impute the peaks list data</i> |
|---------------|-----------------------------------|

---

### Description

Impute the peaks list data

### Usage

```
getimputation(list, method = "l")
```

### Arguments

|        |                                                                                                                                                                                                                                          |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| list   | list with data as peaks list, mz, rt and group information                                                                                                                                                                               |
| method | 'r' means remove, 'l' means use half the minimum of the values across the peaks list, 'mean' means mean of the values across the samples, 'median' means median of the values across the samples, '0' means 0, '1' means 1. Default 'l'. |

**Value**

list with imputed peaks

**See Also**

[getdoe](#)

**Examples**

```
data(list)
getimputation(list)
```

---

|                |                                                                                                                    |
|----------------|--------------------------------------------------------------------------------------------------------------------|
| getintegration | <i>getintegration was mainly used for get the integration of certain ion's chromatogram data and plot the data</i> |
|----------------|--------------------------------------------------------------------------------------------------------------------|

---

**Description**

getintegration was mainly used for get the integration of certain ion's chromatogram data and plot the data

**Usage**

```
getintegration(
  data,
  rt = c(8.3, 9),
  n = 5,
  m = 5,
  slope = c(2, 2),
  baseline = 10,
  noslope = TRUE,
  smoothit = TRUE,
  half = FALSE
)
```

**Arguments**

|          |                                                                                                  |
|----------|--------------------------------------------------------------------------------------------------|
| data     | file should be a dataframe with the first column RT and second column intensity of the SIM ions. |
| rt       | a rough RT range contained only one peak to get the area                                         |
| n        | points in the moving average smooth box, default value is 5                                      |
| m        | numbers of points for regression to get the slope                                                |
| slope    | the threshold value for start/stop peak as percentage of max slope                               |
| baseline | numbers of the points for the baseline of the signal                                             |
| noslope  | logical, if using a horizon line to get area or not                                              |
| smoothit | logical, if using an average smooth box or not. If using, n will be used                         |
| half     | logical, if using the left half peak to calculate the area                                       |

**Value**

integration data such as peak area, peak height, signal and the slope data.

**Examples**

```
## Not run:  
list <- getintegration(data)  
  
## End(Not run)
```

---

|                  |                                                          |
|------------------|----------------------------------------------------------|
| getisotopologues | <i>Get the selected isotopologues at certain MS data</i> |
|------------------|----------------------------------------------------------|

---

**Description**

Get the selected isotopologues at certain MS data

**Usage**

```
getisotopologues(formula = "C6H11O6", charge = 1, width = 0.3, cutoff = 0.05)
```

**Arguments**

|         |                                                                                                |
|---------|------------------------------------------------------------------------------------------------|
| formula | the molecular formula. 'C6H11O6' as default                                                    |
| charge  | the charge of that molecular. 1 in EI mode as default                                          |
| width   | the width of the peak width on mass spectrum. 0.3 as default for low resolution mass spectrum. |
| cutoff  | numeric, minimum relative abundance (fraction of base peak) to consider, default 0.05 (5%).    |

**Examples**

```
## Not run:  
# show isotopologues  
getisotopologues(formula = 'C6H11O6', charge = 1, width = 0.3)  
  
## End(Not run)
```

---

|         |                                                                                                                                   |
|---------|-----------------------------------------------------------------------------------------------------------------------------------|
| getmass | <i>Get the exact mass of the isotopologues from a chemical formula or reaction's isotope patterns with the highest abundances</i> |
|---------|-----------------------------------------------------------------------------------------------------------------------------------|

---

**Description**

Get the exact mass of the isotopologues from a chemical formula or reaction's isotope patterns with the highest abundances

**Usage**

```
getmass(data)
```

**Arguments**

|      |                                                    |
|------|----------------------------------------------------|
| data | a chemical formula or reaction e.g. 'Cl-H', 'C2H4' |
|------|----------------------------------------------------|

**Value**

numerical vector

---

|               |                                                   |
|---------------|---------------------------------------------------|
| getmassdefect | <i>Get mass defect with certain scaled factor</i> |
|---------------|---------------------------------------------------|

---

**Description**

Get mass defect with certain scaled factor

**Usage**

```
getmassdefect(mass, sf)
```

**Arguments**

|      |                |
|------|----------------|
| mass | vector of mass |
| sf   | scaled factors |

**Value**

dataframe with mass, scaled mass and scaled mass defect

**See Also**

[plotkms](#)

**Examples**

```
mass <- c(100.1022, 245.2122, 267.3144, 400.1222, 707.2294)
sf <- 0.9988
mf <- getmassdefect(mass, sf)
```

---

**getmdh***Get the high order unit based Mass Defect*

---

**Description**

Get the high order unit based Mass Defect

**Usage**

```
getmdh(mz, cus = c("CH2, H2"), method = "round")
```

**Arguments**

|        |                                             |
|--------|---------------------------------------------|
| mz     | numeric vector for exact mass               |
| cus    | chemical formula or reaction                |
| method | you could use 'round', 'floor' or 'ceiling' |

**Value**

high order Mass Defect with details

**Examples**

```
## Not run:
getmdh(getmass('C2H4'))

## End(Not run)
```

---

**getmdr***Get the raw Mass Defect*

---

**Description**

Get the raw Mass Defect

**Usage**

```
getmdr(mz)
```

**Arguments**

mz                      numeric vector for exact mass

**Value**

raw Mass Defect

**Examples**

```
getmdr(28.0313)
```

---

|            |                                                                                        |
|------------|----------------------------------------------------------------------------------------|
| getms1anno | <i>Annotation of MS1 data by compounds database by predefined paired mass distance</i> |
|------------|----------------------------------------------------------------------------------------|

---

**Description**

Annotation of MS1 data by compounds database by predefined paired mass distance

**Usage**

```
getms1anno(pmd, mz, ppm = 10, db = NULL)
```

**Arguments**

pmd                      adducts formula or paired mass distance for ions

mz                        unknown mass to charge ratios vector

ppm                       mass accuracy

db                        compounds database as dataframe. Two required columns are name and monoisotopic molecular weight with column names of name and mass

**Value**

list or data frame

---

|        |                                                                |
|--------|----------------------------------------------------------------|
| getMSP | <i>read in MSP file as list for ms/ms or ms(EI) annotation</i> |
|--------|----------------------------------------------------------------|

---

**Description**

read in MSP file as list for ms/ms or ms(EI) annotation

**Usage**

```
getMSP(file)
```

**Arguments**

|      |                           |
|------|---------------------------|
| file | the path to your MSP file |
|------|---------------------------|

**Value**

list a list with MSP information for annotation

---

|            |                                                 |
|------------|-------------------------------------------------|
| getmzrtcsv | <i>Covert the peaks list csv file into list</i> |
|------------|-------------------------------------------------|

---

**Description**

Covert the peaks list csv file into list

**Usage**

```
getmzrtcsv(path)
```

**Arguments**

|      |                           |
|------|---------------------------|
| path | the path to your csv file |
|------|---------------------------|

**Value**

list with rtmz profile and group information as the first row

**See Also**

[getMSP](#)

---

|                |                                                               |
|----------------|---------------------------------------------------------------|
| getoverlappeak | <i>Get the overlap peaks by mass and retention time range</i> |
|----------------|---------------------------------------------------------------|

---

**Description**

Get the overlap peaks by mass and retention time range

**Usage**

```
getoverlappeak(list1, list2)
```

**Arguments**

|       |                                                                                               |
|-------|-----------------------------------------------------------------------------------------------|
| list1 | list with data as peaks list, mz, rt, mzrange, rtrange and group information to be overlapped |
| list2 | list with data as peaks list, mz, rt, mzrange, rtrange and group information to overlap       |

**Value**

logical index for list 1's peaks

**See Also**

[getimputation](#), [getdoe](#)

---

|       |                                              |
|-------|----------------------------------------------|
| getpn | <i>Merge positive and negative mode data</i> |
|-------|----------------------------------------------|

---

**Description**

Merge positive and negative mode data

**Usage**

```
getpn(pos, neg, ppm = 5, pmd = 2.02, digits = 2, cutoff = 0.9)
```

**Arguments**

|        |                                                                                                         |
|--------|---------------------------------------------------------------------------------------------------------|
| pos    | a list with mzrt profile collected from positive mode. The sample order should match the negative mode. |
| neg    | a list with mzrt profile collected from negative mode. The sample order should match the positive mode. |
| ppm    | pmd mass accuracy, default 5                                                                            |
| pmd    | numeric or numeric vector                                                                               |
| digits | mass or mass to charge ratio accuracy for pmd, default 2                                                |
| cutoff | correlation coefficients, default 0.9                                                                   |

**Value**

mzrt object with group information from pos mode

---

|          |                                                                                                          |
|----------|----------------------------------------------------------------------------------------------------------|
| getpower | <i>Get the index with power restriction for certain study with BH adjusted p-value and certain power</i> |
|----------|----------------------------------------------------------------------------------------------------------|

---

**Description**

Get the index with power restriction for certain study with BH adjusted p-value and certain power

**Usage**

```
getpower(list, pt = 0.05, qt = 0.05, power = 0.8, imputation = "1")
```

**Arguments**

|            |                                                            |
|------------|------------------------------------------------------------|
| list       | list with data as peaks list, mz, rt and group information |
| pt         | p value threshold, default 0.05                            |
| qt         | q value threshold, BH adjust, default 0.05                 |
| power      | power cutoff, default 0.8                                  |
| imputation | parameters for 'getimputation' function method             |

**Value**

list with current power and sample numbers for each peaks

**See Also**

[getimputation](#), [getdoe](#)

**Examples**

```
data(list)
getpower(list)
```

---

|        |                                                              |
|--------|--------------------------------------------------------------|
| getpqi | <i>Compute pooled QC linear index according to run order</i> |
|--------|--------------------------------------------------------------|

---

**Description**

Compute pooled QC linear index according to run order

**Usage**

```
getpqi(data, order, n = 5)
```

**Arguments**

|       |                                                              |
|-------|--------------------------------------------------------------|
| data  | peaks intensity list with row as peaks and column as samples |
| order | run order of pooled QC samples                               |
| n     | samples numbers used for linear regression                   |

**Value**

vector for the peaks proportion with significant changes in linear regression after FDR control.

---

|             |                                                                |
|-------------|----------------------------------------------------------------|
| getrangecsv | <i>Get a mzrt list and/or save mz and rt range as csv file</i> |
|-------------|----------------------------------------------------------------|

---

**Description**

Get a mzrt list and/or save mz and rt range as csv file

**Usage**

```
getrangecsv(list, name, ...)
```

**Arguments**

|      |                                                            |
|------|------------------------------------------------------------|
| list | list with data as peaks list, mz, rt and group information |
| name | result name for csv and/or eic file, default NULL          |
| ...  | other parameters for 'write.table'                         |

**Value**

NULL, csv file

---

|           |                                                               |
|-----------|---------------------------------------------------------------|
| getretcor | <i>Perform peaks list alignment and return features table</i> |
|-----------|---------------------------------------------------------------|

---

**Description**

Perform peaks list alignment and return features table

**Usage**

```
getretcor(list, ts = 1, ppm = 10, delbart = 5, FUN)
```

**Arguments**

|         |                                                                                                                                 |
|---------|---------------------------------------------------------------------------------------------------------------------------------|
| list    | each element should be a data.frame with mz, rt and intensity as m/z, retention time in seconds and intensity of certain peaks. |
| ts      | template sample index in the list, default 1                                                                                    |
| ppm     | mass accuracy, default 10                                                                                                       |
| delbart | retention time shift table, default 5 seconds                                                                                   |
| FUN     | function to deal with multiple aligned peaks from one sample                                                                    |

**Value**

mzrt object without group information

---

|        |                                     |
|--------|-------------------------------------|
| getrmd | <i>Get the Relative Mass Defect</i> |
|--------|-------------------------------------|

---

**Description**

Get the Relative Mass Defect

**Usage**

```
getrmd(mz)
```

**Arguments**

|    |                               |
|----|-------------------------------|
| mz | numeric vector for exact mass |
|----|-------------------------------|

**Value**

Relative Mass Defect

**Examples**

```
getrmd(28.0313)
```

---

gifmr*plot scatter plot for rt-mz profile and output gif file for multiple groups*

---

**Description**

plot scatter plot for rt-mz profile and output gif file for multiple groups

**Usage**

```
gifmr(  
  list,  
  ms = c(100, 500),  
  rsdcf = 30,  
  inscf = 5,  
  imputation = "1",  
  name = "test",  
  ...  
)
```

**Arguments**

|            |                                                                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| list       | list with data as peaks list, mz, rt and group information                                                                                                      |
| ms         | the mass range to plot the data                                                                                                                                 |
| rsdcf      | the rsd cutoff of all peaks in all group                                                                                                                        |
| inscf      | Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5 |
| imputation | parameters for 'getimputation' function method                                                                                                                  |
| name       | file name for gif file, default test                                                                                                                            |
| ...        | parameters for 'plot' function                                                                                                                                  |

**Value**

gif file

**Examples**

```
## Not run:  
data(list)  
gifmr(list)  
  
## End(Not run)
```

## Description

Performs high-resolution mass filtering by matching experimental mass spectral peaks against theoretical isotope patterns derived from one or more candidate chemical formulae. Calculates forward HRMF score, reverse (MSP) score, and Figure of Merit (FoM) for each candidate.

## Usage

```
HRMF(  
  msp,  
  formula,  
  charge = 1,  
  adduct = NULL,  
  mass_accuracy = 5,  
  intensity_cutoff = 1,  
  IR_RelAb_cutoff = 1,  
  detailed = FALSE  
)
```

## Arguments

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| msp              | list. A single compound entry as returned by <a href="#">getMSP</a> , containing at least a spectra element with columns mz and intensity.                                                                                                                                                                                                                                                                                                 |
| formula          | character vector. One or more candidate chemical formulae to evaluate.                                                                                                                                                                                                                                                                                                                                                                     |
| charge           | integer. Charge state: 1 for positive, -1 for negative, 0 for neutral. Default 1 (radical cation in EI). Ignored when adduct is supplied.                                                                                                                                                                                                                                                                                                  |
| adduct           | character vector of adduct names for singly-charged ESI ions (e.g. "[M+H]+", c("[M+H]+", "[M+Na]+")), or a named numeric vector of custom mass deltas in Da with names ending in "+" or "-" (e.g. c("[M+MeOH]+" = 33.033491)). Default NULL keeps the legacy radical-ion/neutral behaviour governed by charge. Built-in adducts: "[M+H]+", "[M+Na]+", "[M+NH4]+", "[M+K]+", "[M+H-H2O]+", "[M-H]-", "[M+Cl]-", "[M+HCOO]-", "[M+CH3COO]-". |
| mass_accuracy    | numeric. Mass accuracy in ppm. Default 5.                                                                                                                                                                                                                                                                                                                                                                                                  |
| intensity_cutoff | numeric. Minimum absolute intensity to retain a peak. Default 1.                                                                                                                                                                                                                                                                                                                                                                           |
| IR_RelAb_cutoff  | numeric. Relative abundance cutoff (%) for theoretical isotopologues. Default 1.                                                                                                                                                                                                                                                                                                                                                           |
| detailed         | logical. If TRUE, return detailed list with all_ions, compound, and HRMF_scores for each formula. If FALSE (default), return a summary data.frame.                                                                                                                                                                                                                                                                                         |

## Details

The method is based on Kwiecien et al. (2015) [doi:10.1021/acs.analchem.5b01503](https://doi.org/10.1021/acs.analchem.5b01503).

Unlike the original MSxplorer implementation, this version uses the native HORIZON (Heavy-first Ordered Recursive Inference with Zero-loop Optimal Navigation) engine via Rcpp for both high-performance formula decomposition and isotope pattern calculation, requiring no external dependencies.

The input msp should be a single entry from the list returned by `getMSP`. For batch processing of entire MSP files, see `getHRMF`.

For EI (GC-MS) radical ions use the default charge argument. For ESI (LC-MS/MS) data with even-electron adduct ions such as  $[M+H]^+$  or  $[M-H]^-$ , supply adduct so that fragment  $m/z$  values are converted internally; the adduct should describe how fragment ions are formed (usually the same as the precursor adduct for singly-charged fragmentation).

## Value

If `detailed = FALSE`, a `data.frame` with one row per candidate formula (and per adduct, if supplied) and columns: `Candidate`, `Adduct`, `peak_count_forw`, `df_theortomsp`, `HRMF_theor_score`, `peak_count_rev`, `df_msptotheor`, `HRMF_msp_score`, `FoM`. If `detailed = TRUE`, a named list of detailed results per formula/adduct.

## See Also

`getHRMF` for batch processing, `getMSP` for reading MSP files.

## Examples

```
## Not run:
# Read MSP file and run HRMF on the first compound (EI radical cation)
msp_data <- getMSP("spectrum.msp")
result <- HRMF(msp_data[[1]], formula = "C8H11NO")

# Compare multiple candidates
result <- HRMF(msp_data[[1]], formula = c("C8H11NO", "C7H9NO2"))

# LC-MS/MS with protonated fragments
result <- HRMF(msp_data[[1]], formula = "C8H10N4O2", adduct = "[M+H]+")

# Multiple candidate adducts are scored separately
result <- HRMF(msp_data[[1]], formula = "C8H10N4O2",
               adduct = c("[M+H]+", "[M+Na]+"))

## End(Not run)
```

---

|             |                                                                       |
|-------------|-----------------------------------------------------------------------|
| integration | <i>Just integrate data according to fixed rt and fixed noise area</i> |
|-------------|-----------------------------------------------------------------------|

---

**Description**

Just integrate data according to fixed rt and fixed noise area

**Usage**

```
integration(data, rt = c(8.3, 9), brt = c(8.3, 8.4), smoothit = TRUE)
```

**Arguments**

|          |                                                                                                  |
|----------|--------------------------------------------------------------------------------------------------|
| data     | file should be a dataframe with the first column RT and second column intensity of the SIM ions. |
| rt       | a rough RT range contained only one peak to get the area                                         |
| brt      | a rough RT range contained only one peak and enough noises to get the area                       |
| smoothit | logical, if using an average smooth box or not. If using, n will be used                         |

**Value**

area integration data

**Examples**

```
## Not run:  
area <- integration(data)  
  
## End(Not run)
```

---

|      |                  |
|------|------------------|
| list | <i>Demo data</i> |
|------|------------------|

---

**Description**

Demo data

**Usage**

```
data(list)
```

**Format**

A list object with data, mass to charge ratio, retention time and group information. The list is generated from faahKO package.

|    |                                          |
|----|------------------------------------------|
| ma | <i>filter data by average moving box</i> |
|----|------------------------------------------|

---

**Description**

filter data by average moving box

**Usage**

```
ma(x, n)
```

**Arguments**

|   |                                                  |
|---|--------------------------------------------------|
| x | a vector                                         |
| n | A number to identify the size of the moving box. |

**Value**

The filtered data

**Examples**

```
ma(rnorm(1000),5)
```

---

|        |                             |
|--------|-----------------------------|
| matrix | <i>Demo raw data matrix</i> |
|--------|-----------------------------|

---

**Description**

Demo raw data matrix

**Usage**

```
data(matrix)
```

**Format**

A matrix object from raw mass spectrometry data. The list is generated from faahKO package.

---

|        |                                                                          |
|--------|--------------------------------------------------------------------------|
| plotcc | <i>Plot the calibration curve with error bar, r squared and equation</i> |
|--------|--------------------------------------------------------------------------|

---

**Description**

Plot the calibration curve with error bar, r squared and equation

**Usage**

```
plotcc(x, y, upper, lower = upper, ...)
```

**Arguments**

|       |                                |
|-------|--------------------------------|
| x     | concentration                  |
| y     | response                       |
| upper | upper error bar                |
| lower | lower error bar                |
| ...   | parameters for 'plot' function |

**Examples**

```
## Not run:  
plotcc(x,y,upper)  
  
## End(Not run)
```

---

|         |                                              |
|---------|----------------------------------------------|
| plotden | <i>plot the density for multiple samples</i> |
|---------|----------------------------------------------|

---

**Description**

plot the density for multiple samples

**Usage**

```
plotden(data, lv, index = NULL, name = NULL, lwd = 1, ...)
```

**Arguments**

|       |                                            |
|-------|--------------------------------------------|
| data  | data row as peaks and column as samples    |
| lv    | group information                          |
| index | index for selected peaks                   |
| name  | name on the figure for samples             |
| lwd   | the line width for density plot, default 1 |
| ...   | parameters for 'plot' function             |

**Examples**

```
data(list)
plotden(list$data, lv = as.character(list$group$sample_group),ylim = c(0,1))
```

---

|           |                                                             |
|-----------|-------------------------------------------------------------|
| plotdwtus | <i>plot density weighted intensity for multiple samples</i> |
|-----------|-------------------------------------------------------------|

---

**Description**

plot density weighted intensity for multiple samples

**Usage**

```
plotdwtus(list, n = 512, ...)
```

**Arguments**

|      |                                                                                          |
|------|------------------------------------------------------------------------------------------|
| list | list with data as peaks list, mz, rt and group information                               |
| n    | the number of equally spaced points at which the density is to be estimated, default 512 |
| ...  | parameters for 'plot' function                                                           |

**Value**

Density weighted intensity for multiple samples

**Examples**

```
data(list)
plotdwtus(list)
```

---

|         |                                                                  |
|---------|------------------------------------------------------------------|
| plotEIC | <i>Plot extracted ion chromatograms from raw mzML/mzXML data</i> |
|---------|------------------------------------------------------------------|

---

**Description**

Reads mzML/mzXML raw data and plots extracted ion chromatograms (EIC) for a list of target m/z values at MS1 or MS2 level. Uses **RaMS** for lightweight data access and **plotly** for interactive visualization.

**Usage**

```
plotEIC(filepath, featlist, diff = 0.005)
```

**Arguments**

|          |                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------|
| filepath | character. Path to an mzML or mzXML file.                                                         |
| featlist | data.frame with columns: name (feature label), mz (target m/z), ms_level (either "ms1" or "ms2"). |
| diff     | numeric. Half-width of the m/z extraction window in Da. Default 0.005.                            |

**Value**

A **plotly** object with overlaid extracted ion chromatograms.

**Examples**

```
## Not run:
featlist <- data.frame(
  name = c("target1", "target2"),
  mz = c(300.1234, 350.5678),
  ms_level = c("ms1", "ms2")
)
plotEIC("sample.mzML", featlist)

## End(Not run)
```

---

plotgroup

*Plot the response group of GC-MS*

---

**Description**

Plot the response group of GC-MS

**Usage**

```
plotgroup(data, threshold = 2)
```

**Arguments**

|           |                                                                    |
|-----------|--------------------------------------------------------------------|
| data      | imported data matrix of GC-MS                                      |
| threshold | the threshold of the response (log based 10) to separate the group |

**Value**

list linear regression model for the data matrix

**Examples**

```
## Not run:
data(matrix)
plotgroup(matrix)

## End(Not run)
```

---

|          |                                                                                                                   |
|----------|-------------------------------------------------------------------------------------------------------------------|
| plothist | <i>Plot the density of the GC-MS data with EM algorithm to separate the data into two log normal distribution</i> |
|----------|-------------------------------------------------------------------------------------------------------------------|

---

**Description**

Plot the density of the GC-MS data with EM algorithm to separate the data into two log normal distribution

**Usage**

```
plothist(data)
```

**Arguments**

|      |                               |
|------|-------------------------------|
| data | imported data matrix of GC-MS |
|------|-------------------------------|

**Examples**

```
## Not run:  
# generate a matrix from raw data with row as m/z and column as retention time  
plothist(matrix)  
  
## End(Not run)
```

---

|        |                                          |
|--------|------------------------------------------|
| plothm | <i>Plot the heatmap of mzrt profiles</i> |
|--------|------------------------------------------|

---

**Description**

Plot the heatmap of mzrt profiles

**Usage**

```
plothm(data, lv, index = NULL)
```

**Arguments**

|       |                                         |
|-------|-----------------------------------------|
| data  | data row as peaks and column as samples |
| lv    | group information                       |
| index | index for selected peaks                |

**Examples**

```
data(list)  
plothm(list$data, lv = as.factor(list$group$sample_group))
```

---

|         |                                            |
|---------|--------------------------------------------|
| plotint | <i>plot the information of integration</i> |
|---------|--------------------------------------------|

---

**Description**

plot the information of integration

**Usage**

```
plotint(list, name = NULL)
```

**Arguments**

|      |                         |
|------|-------------------------|
| list | list from getinteagtion |
| name | the title of the plot   |

**Examples**

```
## Not run:  
list <- getinteagtion(rawdata)  
plotint(list)  
  
## End(Not run)
```

---

|              |                                                  |
|--------------|--------------------------------------------------|
| plotintslope | <i>plot the slope information of integration</i> |
|--------------|--------------------------------------------------|

---

**Description**

plot the slope information of integration

**Usage**

```
plotintslope(list, name = NULL)
```

**Arguments**

|      |                          |
|------|--------------------------|
| list | list from getintegration |
| name | the title of the plot    |

**Examples**

```
## Not run:  
list <- getinteragtion(rawdata)  
plotintslope(list)  
  
## End(Not run)
```

---

|         |                                              |
|---------|----------------------------------------------|
| plotkms | <i>plot the kendrick mass defect diagram</i> |
|---------|----------------------------------------------|

---

**Description**

plot the kendrick mass defect diagram

**Usage**

```
plotkms(data, cutoff = 1000)
```

**Arguments**

|        |                          |
|--------|--------------------------|
| data   | vector with the name m/z |
| cutoff | remove the low intensity |

**See Also**

[getmassdefect](#)

**Examples**

```
## Not run:
mz <- c(10000, 5000, 20000, 100, 40000)
names(mz) <- c(100.1022, 245.2122, 267.3144, 400.1222, 707.2294)
plotkms(mz)

## End(Not run)
```

---

|        |                                                            |
|--------|------------------------------------------------------------|
| plotmr | <i>plot the scatter plot for peaks list with threshold</i> |
|--------|------------------------------------------------------------|

---

**Description**

plot the scatter plot for peaks list with threshold

**Usage**

```
plotmr(
  list,
  rt = NULL,
  ms = NULL,
  inscf = 5,
  rsdcf = 30,
  imputation = "1",
  ...
)
```

**Arguments**

|            |                                                                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| list       | list with data as peaks list, mz, rt and group information                                                                                                      |
| rt         | vector range of the retention time                                                                                                                              |
| ms         | vector vector range of the m/z                                                                                                                                  |
| inscf      | Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5 |
| rsdcf      | the rsd cutoff of all peaks in all group, default 30                                                                                                            |
| imputation | parameters for 'getimputation' function method                                                                                                                  |
| ...        | parameters for 'plot' function                                                                                                                                  |

**Value**

data fit the cutoff

**Examples**

```
data(list)
plotmr(list)
```

---

|         |                                                                                    |
|---------|------------------------------------------------------------------------------------|
| plotmrc | <i>plot the diff scatter plot for peaks list with threshold between two groups</i> |
|---------|------------------------------------------------------------------------------------|

---

**Description**

plot the diff scatter plot for peaks list with threshold between two groups

**Usage**

```
plotmrc(list, ms = c(100, 800), inscf = 5, rsdcf = 30, imputation = "l", ...)
```

**Arguments**

|            |                                                                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| list       | list with data as peaks list, mz, rt and group information                                                                                                      |
| ms         | the mass range to plot the data                                                                                                                                 |
| inscf      | Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5 |
| rsdcf      | the rsd cutoff of all peaks in all group                                                                                                                        |
| imputation | parameters for 'getimputation' function method                                                                                                                  |
| ...        | parameters for 'plot' function                                                                                                                                  |

**Examples**

```
data(list)
plotmrc(list)
```

---

|        |                                                 |
|--------|-------------------------------------------------|
| plotms | <i>plot GC/LC-MS data as a heatmap with TIC</i> |
|--------|-------------------------------------------------|

---

**Description**

plot GC/LC-MS data as a heatmap with TIC

**Usage**

```
plotms(data, log = FALSE)
```

**Arguments**

|      |                                           |
|------|-------------------------------------------|
| data | imported data matrix of GC-MS             |
| log  | transform the intensity into log based 10 |

**Value**

heatmap

**Examples**

```
## Not run:  
png('test.png')  
plotms(matrix)  
dev.off()  
  
## End(Not run)
```

---

|        |                                           |
|--------|-------------------------------------------|
| plotmz | <i>plot GC/LC-MS data as scatter plot</i> |
|--------|-------------------------------------------|

---

**Description**

plot GC/LC-MS data as scatter plot

**Usage**

```
plotmz(data, inscf = 3.5, ...)
```

**Arguments**

|       |                                             |
|-------|---------------------------------------------|
| data  | imported data matrix of GC-MS               |
| inscf | Log intensity cutoff for peaks, default 3.5 |
| ...   | parameters for 'plot' function              |

**Value**

scatter plot

**Examples**

```
## Not run:  
data(matrix)  
png('test.png')  
plotmz(matrix)  
dev.off()  
  
## End(Not run)
```

---

plotpca

*plot the PCA for multiple samples*

---

**Description**

plot the PCA for multiple samples

**Usage**

```
plotpca(  
  data,  
  lv = NULL,  
  index = NULL,  
  center = TRUE,  
  scale = TRUE,  
  xrange = NULL,  
  yrange = NULL,  
  pch = NULL,  
  ...  
)
```

**Arguments**

|        |                                                                               |
|--------|-------------------------------------------------------------------------------|
| data   | data row as peaks and column as samples                                       |
| lv     | group information                                                             |
| index  | index for selected peaks                                                      |
| center | parameters for PCA                                                            |
| scale  | parameters for scale                                                          |
| xrange | x axis range for return samples, default NULL                                 |
| yrange | y axis range for return samples, default NULL                                 |
| pch    | default pch would be the first character of group information or samples name |
| ...    | other parameters for 'plot' function                                          |

**Value**

if xrange and yrange are not NULL, return file name of all selected samples on 2D score plot

**Examples**

```
data(list)
plotpca(list$data, lv = as.character(list$group$sample_group))
```

---

plotpeak

*plot intensity of peaks across samples or samples across peaks*


---

**Description**

plot intensity of peaks across samples or samples across peaks

**Usage**

```
plotpeak(data, lv = NULL, indexx = NULL, indexy = NULL, ...)
```

**Arguments**

|        |                                 |
|--------|---------------------------------|
| data   | matrix                          |
| lv     | factor vector for the column    |
| indexx | index for matrix row            |
| indexy | index for matrix column         |
| ...    | parameters for 'title' function |

**Value**

parallel coordinates plot

**Examples**

```
data(list)
# selected peaks across samples
plotpeak(t(list$data), lv = as.factor(c(rep(1,5),rep(2,nrow(list$data)-5))),1:10,1:10)
# selected samples across peaks
plotpeak(list$data, lv = as.factor(list$group$sample_group),1:10,1:10)
```

---

|           |                                    |
|-----------|------------------------------------|
| plotridge | <i>plot ridgeline density plot</i> |
|-----------|------------------------------------|

---

**Description**

plot ridgeline density plot

**Usage**

```
plotridge(data, lv = NULL, indexx = NULL, indexy = NULL, ...)
```

**Arguments**

|        |                                 |
|--------|---------------------------------|
| data   | matrix                          |
| lv     | factor vector for the column    |
| indexx | index for matrix row            |
| indexy | index for matrix column         |
| ...    | parameters for 'title' function |

**Value**

ridgeline density plot

**Examples**

```
data(list)
plotridge(t(list$data),indexy=c(1:10),xlab = 'Intensity',ylab = 'peaks')
plotridge(log(list$data),as.factor(list$group$sample_group),xlab = 'Intensity',ylab = 'peaks')
```

---

|            |                                                                       |
|------------|-----------------------------------------------------------------------|
| plotridges | <i>Relative Log Abundance Ridge (RLAR) plots for samples or peaks</i> |
|------------|-----------------------------------------------------------------------|

---

**Description**

Relative Log Abundance Ridge (RLAR) plots for samples or peaks

**Usage**

```
plotridges(data, lv, type = "g")
```

**Arguments**

|      |                                                                     |
|------|---------------------------------------------------------------------|
| data | data row as peaks and column as samples                             |
| lv   | factor vector for the group information of samples                  |
| type | 'g' means group median based, other means all samples median based. |

**Value**

Relative Log Abundance Ridge(RLA) plots

**Examples**

```
data(list)
plotridges(list$data, as.factor(list$group$sample_group))
```

---

|         |                                           |
|---------|-------------------------------------------|
| plotrla | <i>Relative Log Abundance (RLA) plots</i> |
|---------|-------------------------------------------|

---

**Description**

Relative Log Abundance (RLA) plots

**Usage**

```
plotrla(data, lv, type = "g", ...)
```

**Arguments**

- data            data row as peaks and column as samples
- lv            factor vector for the group information
- type           'g' means group median based, other means all samples median based.
- ...           parameters for boxplot

**Value**

Relative Log Abundance (RLA) plots

**Examples**

```
data(list)
plotrla(list$data, as.factor(list$group$sample_group))
```

---

|         |                                                            |
|---------|------------------------------------------------------------|
| plotrsd | <i>plot the rsd influences of data in different groups</i> |
|---------|------------------------------------------------------------|

---

**Description**

plot the rsd influences of data in different groups

**Usage**

```
plotrsd(list, ms = c(100, 800), inscf = 5, rsdcf = 100, imputation = "1", ...)
```

**Arguments**

|            |                                                                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| list       | list with data as peaks list, mz, rt and group information                                                                                                      |
| ms         | the mass range to plot the data                                                                                                                                 |
| inscf      | Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5 |
| rsdcf      | the rsd cutoff of all peaks in all group                                                                                                                        |
| imputation | parameters for 'getimputation' function method                                                                                                                  |
| ...        | other parameters for 'plot' function                                                                                                                            |

**Examples**

```
data(list)
plotrsd(list)
```

---

|         |                                              |
|---------|----------------------------------------------|
| plotrug | <i>plot 1-d density for multiple samples</i> |
|---------|----------------------------------------------|

---

**Description**

plot 1-d density for multiple samples

**Usage**

```
plotrug(data, lv = NULL, indexx = NULL, indexy = NULL, ...)
```

**Arguments**

|        |                                 |
|--------|---------------------------------|
| data   | matrix                          |
| lv     | factor vector for the column    |
| indexx | index for matrix row            |
| indexy | index for matrix column         |
| ...    | parameters for 'title' function |

**Examples**

```
data(list)
plotrug(list$data)
plotrug(log(list$data), lv = as.factor(list$group$sample_group))
```

plotsms

*Plot the intensity distribution of GC-MS***Description**

Plot the intensity distribution of GC-MS

**Usage**

```
plotsms(meanmatrix, rsdmatrix)
```

**Arguments**

|            |                                         |
|------------|-----------------------------------------|
| meanmatrix | mean data matrix of GC-MS(n=5)          |
| rsdmatrix  | standard deviation matrix of GC-MS(n=5) |

**Examples**

```
## Not run:
plotsms(meanmatrix,rsdmatrix)

## End(Not run)
```

plotsub

*Plot the background of data***Description**

Plot the background of data

**Usage**

```
plotsub(data)
```

**Arguments**

|      |                               |
|------|-------------------------------|
| data | imported data matrix of GC-MS |
|------|-------------------------------|

**Examples**

```
## Not run:
plotsub(matrix)

## End(Not run)
```

---

|       |                                                                              |
|-------|------------------------------------------------------------------------------|
| plott | <i>plot GC-MS data as a heatmap for constant speed of temperature rising</i> |
|-------|------------------------------------------------------------------------------|

---

**Description**

plot GC-MS data as a heatmap for constant speed of temperature rising

**Usage**

```
plott(data, log = FALSE, temp = c(100, 320))
```

**Arguments**

|      |                                           |
|------|-------------------------------------------|
| data | imported data matrix of GC-MS             |
| log  | transform the intensity into log based 10 |
| temp | temperature range for constant speed      |

**Value**

heatmap

**Examples**

```
## Not run:  
plott(matrix)  
  
## End(Not run)
```

---

|         |                                          |
|---------|------------------------------------------|
| plottic | <i>Plot Total Ion Chromatogram (TIC)</i> |
|---------|------------------------------------------|

---

**Description**

Plot Total Ion Chromatogram (TIC)

**Usage**

```
plottic(data, n = FALSE)
```

**Arguments**

|      |                               |
|------|-------------------------------|
| data | imported data matrix of GC-MS |
| n    | logical smooth or not         |

**Value**

plot

**Examples**

```
## Not run:  
plottic(matrix)  
  
## End(Not run)
```

---

plotTopMS1Peaks

*Extract top MS1 ions from MS2 EIC interactively*

---

**Description**

A Shiny app that displays extracted ion chromatograms from MS2 data. Click on a peak to select a retention time window, then extract the most intense MS1 ions from that window and overlay their chromatograms.

**Usage**

```
plotTopMS1Peaks(  
  filepath,  
  featlist,  
  numTopIons = 10,  
  diff = 0.01,  
  rtWindow = 0.3  
)
```

**Arguments**

|            |                                                                              |
|------------|------------------------------------------------------------------------------|
| filepath   | character. Path to an mzML or mzXML file.                                    |
| featlist   | data.frame with columns: name, mz, ms_level.                                 |
| numTopIons | integer. Number of most intense MS1 ions to extract. Default 10.             |
| diff       | numeric. Half-width of m/z extraction window (Da). Default 0.01.             |
| rtWindow   | numeric. Half-width of RT window (seconds) around clicked peak. Default 0.3. |

**Value**

Opens an interactive Shiny app in the browser.

## Examples

```
## Not run:
frags <- data.frame(
  name = c("Br79", "Br81"),
  mz = c(78.9183, 80.9163),
  ms_level = c("ms2", "ms2")
)
plotTopMS1Peaks("sample.mzML", frags, numTopIons = 3)

## End(Not run)
```

---

plotTopMS2Peaks

*Extract top MS2 ions from MS1 EIC interactively*

---

## Description

A Shiny app that displays extracted ion chromatograms from MS1 data. Click on a peak to select a retention time window, then extract the most intense MS2 ions from that window and overlay their chromatograms.

## Usage

```
plotTopMS2Peaks(
  filepath,
  featlist,
  numTopIons = 10,
  diff = 0.01,
  rtWindow = 0.3
)
```

## Arguments

|            |                                                                              |
|------------|------------------------------------------------------------------------------|
| filepath   | character. Path to an mzML or mzXML file.                                    |
| featlist   | data.frame with columns: name, mz, ms_level.                                 |
| numTopIons | integer. Number of most intense MS1 ions to extract. Default 10.             |
| diff       | numeric. Half-width of m/z extraction window (Da). Default 0.01.             |
| rtWindow   | numeric. Half-width of RT window (seconds) around clicked peak. Default 0.3. |

## Value

Opens an interactive Shiny app in the browser.

**Examples**

```
## Not run:
targets <- data.frame(
  name = c("precursor1"),
  mz = c(500.1234),
  ms_level = c("ms1")
)
plotTopMS2Peaks("sample.mzML", targets, numTopIons = 5)

## End(Not run)
```

---

**runMDPlot***Shiny application for interactive mass defect plots analysis*

---

**Description**

Shiny application for interactive mass defect plots analysis

**Usage**

```
runMDPlot()
```

---

**runsccp***Shiny application for Short-Chain Chlorinated Paraffins analysis*

---

**Description**

Shiny application for Short-Chain Chlorinated Paraffins analysis

**Usage**

```
runsccp()
```

---

|      |                                                                                             |
|------|---------------------------------------------------------------------------------------------|
| sccp | <i>Short-Chain Chlorinated Paraffins(SCCPs) peaks information for quantitative analysis</i> |
|------|---------------------------------------------------------------------------------------------|

---

**Description**

A dataset containing the ions, formula, Cl

**Usage**

```
data(sccp)
```

**Format**

A data frame with 24 rows and 8 variables:

**Cl<sub>n</sub>** Chlorine atom numbers

**C<sub>n</sub>** Carbon atom numbers

**formula** molecular formula

**H<sub>n</sub>** hydrogen atom numbers

**ions** [M-Cl]- ions

**m<sub>z</sub>** m/z for the isotopologues with highest intensity

**intensity** abundance of the isotopologues with highest intensity

**Cl<sub>p</sub>** Chlorine contents

---

|               |                                                     |
|---------------|-----------------------------------------------------|
| scoreIsotopes | <i>Calculate Isotopic Pattern Similarity Scores</i> |
|---------------|-----------------------------------------------------|

---

**Description**

Computes modern spectral similarity metrics including Cosine similarity, intensity-weighted dot product, and log-likelihood between observed mass spectral peaks and theoretical isotopic distributions.

**Usage**

```
scoreIsotopes(  
  obs_mz,  
  obs_int,  
  theo_mz,  
  theo_int,  
  tolerance = 0.005,  
  ppm = FALSE  
)
```

**Arguments**

|                        |                                                                  |
|------------------------|------------------------------------------------------------------|
| <code>obs_mz</code>    | Numeric vector of observed m/z values.                           |
| <code>obs_int</code>   | Numeric vector of observed intensities.                          |
| <code>theo_mz</code>   | Numeric vector of theoretical isotopic m/z values.               |
| <code>theo_int</code>  | Numeric vector of theoretical isotopic abundances.               |
| <code>tolerance</code> | Numeric mass tolerance for peak alignment (default: 0.005).      |
| <code>ppm</code>       | Logical indicating whether tolerance is in ppm (default: FALSE). |

**Value**

A list containing:

|                              |                                                                   |
|------------------------------|-------------------------------------------------------------------|
| <code>cosine</code>          | Cosine similarity (unweighted dot product of normalized spectra). |
| <code>weighted_cosine</code> | Mass- and intensity-weighted dot product (MassBank/NIST style).   |
| <code>log_likelihood</code>  | Multinomial log-likelihood of observed peak distribution.         |
| <code>matched_peaks</code>   | Integer count of successfully matched peaks.                      |

**Examples**

```
obs_m <- c(180.0634, 181.0668)
obs_i <- c(100, 6.5)
theo_m <- c(180.0634, 181.0668)
theo_i <- c(1.0, 0.066)
scoreIsotopes(obs_m, obs_i, theo_m, theo_i)
```

---

TBBPA

*Demo data for TBBPA metabolism in Pumpkin*

---

**Description**

Demo data for TBBPA metabolism in Pumpkin

**Usage**

```
data(TBBPA)
```

**Format**

A list object with data, mass to charge ratio, retention time and group information. Three pumpkin seeding root samples' peaks list is extracted by xcms online.

**References**

Hou, X., Yu, M., Liu, A., Wang, X., Li, Y., Liu, J., Schnoor, J.L., Jiang, G., 2019. Glycosylation of Tetrabromobisphenol A in Pumpkin. Environ. Sci. Technol. <https://doi.org/10.1021/acs.est.9b02122>

---

|          |                                       |
|----------|---------------------------------------|
| writeMSP | <i>Write MSP file for NIST search</i> |
|----------|---------------------------------------|

---

**Description**

Write MSP file for NIST search

**Usage**

```
writeMSP(list, name = "unknown", sep = FALSE)
```

**Arguments**

|      |                                                                                                                |
|------|----------------------------------------------------------------------------------------------------------------|
| list | a list with spectra information                                                                                |
| name | name of the compounds                                                                                          |
| sep  | numeric or logical the numbers of spectra in each file and FALSE to include all of the spectra in one msp file |

**Value**

none a MSP file will be created.

**Examples**

```
## Not run:
intensity <- c(10000,20000,10000,30000,5000)
mz <- c(101,143,189,221,234)
writeMSP(list(list(spectra = cbind.data.frame(mz,intensity))), name = 'test')

## End(Not run)
```

# Index

## \* datasets

- list, [31](#)
- matrix, [32](#)
- sccp, [51](#)
- TBBPA, [52](#)

c.mzrt, [3](#)  
checkGoldenRules, [4](#)  
cleanMGF, [5](#)

findline, [6](#)  
findlipid, [7](#)  
findmet, [7](#)  
findohc, [8](#)  
findpfc, [9](#)

getalign, [10](#)  
getalign2, [10](#)  
getcompare, [11](#)  
getcsv, [12](#), [15](#)  
getdoe, [13](#), [18](#), [24](#), [25](#)  
getdwtus, [14](#)  
getfilter, [14](#)  
getformula, [15](#)  
getHRMF, [16](#), [30](#)  
getimputation, [13](#), [15](#), [17](#), [24](#), [25](#)  
getintegration, [18](#)  
getisotopologues, [19](#)  
getmass, [20](#)  
getmassdefect, [20](#), [38](#)  
getmdh, [21](#)  
getmdr, [21](#)  
getms1anno, [22](#)  
getMSP, [6](#), [17](#), [23](#), [23](#), [29](#), [30](#)  
getmzrtcsv, [23](#)  
getoverlappeak, [24](#)  
getpn, [24](#)  
getpower, [13](#), [25](#)  
getpqi, [26](#)  
getrange csv, [26](#)

getretcor, [27](#)  
getrmd, [27](#)  
gifmr, [28](#)

HRMF, [5](#), [6](#), [16](#), [17](#), [29](#)

integration, [31](#)

list, [31](#)

ma, [32](#)  
matrix, [32](#)

plotcc, [33](#)  
plotden, [33](#)  
plotdwtus, [34](#)  
plotEIC, [34](#)  
plotgroup, [35](#)  
plohist, [36](#)  
plohm, [36](#)  
plotint, [37](#)  
plotintslope, [37](#)  
plotkms, [20](#), [38](#)  
plotmr, [38](#)  
plotmrc, [39](#)  
plotms, [40](#)  
plotmz, [40](#)  
plotpca, [41](#)  
plotpeak, [42](#)  
plotridge, [43](#)  
plotridges, [43](#)  
plotrla, [44](#)  
plotrsd, [45](#)  
plotrug, [45](#)  
plotsms, [46](#)  
plotsub, [46](#)  
plott, [47](#)  
plottic, [47](#)  
plotTopMS1Peaks, [48](#)  
plotTopMS2Peaks, [49](#)

runMDPlot, [50](#)

runsccp, [50](#)

sccp, [51](#)

scoreIsotopes, [51](#)

TBBPA, [52](#)

writeMSP, [53](#)